

General Product Description – MS 16-inch Printer Fired Cash Drawer

Radiant Model P000F024

Radiant cash drawer model P000F024 is a custom-designed cash drawer manufactured by M-S Cash Drawer for Radiant Systems. The cash drawer features a full five-bill, five-coin molded till and a printer fired interface with detachable cable. A stainless steel front, three-function lock, and rugged screw on feet all come standard.



Every-Unit-Item Features and Benefits

Feature	Benefit
Detachable Cable	The same drawer can be used with many different types of receipt printers simply by switching interface cables; If your printer requirements ever change, you won't have to replace the whole cash drawer
Printer Driven	Eliminates the need for a power supply or separate power cord
Dual Beveled Media Slots	Quick access to media storage reduces transaction time

Cash Drawer Features

Feature Number P000F024

MS 16-inch Printer Fired Cash Drawer

Includes black 16-inch CD00046 cash drawer with stainless steel front, five-bill/five-coin till, 24V printer fired interface, and detachable cable compatible with receipt printers that have Epson compatible cash drawer kick out ports.

Optional Accessories

CB00318 Spare cash drawer interface cable f/ printers w/ Epson compatible CD ports, 6 ft

CB00319 Cash drawer interface cable for printers with Ithaca compatible CD ports, 6 ft

CB00320 Cash drawer interface cable for printers with Star compatible CD ports, 6 ft

OP00013 Spare/extra 5-bill, 5-coin money till

CD00048 Optional steel locking lid

CD00049 Optional under-the-counter mounting brackets

CD00050 Spare cash drawer foot

CD00020 Spare cash drawer key 010

Specifications

Enclosure	Steel enclosure with black powder coat finish and stainless steel drawer front
Key lock	Three function lock (manual open, electrically on-line, and locked closed)
Till	Five-bill/five-coin
Media slots	Two beveled media slots
Interface	Printer fired; 24VDC solenoid @ 25 ohms
Cable length	6 feet
Tray release	Quick release tray; No tools are required to remove the tray
Dimension	15.9" (W) x 16.7" (L) x 4.36" (H) with feet
Weight	20 lbs
Power	Powered by receipt printer

This document is intended only for internal use by Radiant employees, and may contain information which is privileged, confidential and exempt from disclosure under applicable law. If the reader of this document is not a Radiant employee, you are hereby notified that any dissemination, distribution or copying of this communication is strictly prohibited.



Operating temperature	0 to 50 C
Operating humidity	10% to 90% without condensation
Storage temperature	-20 to 70 C
Storage humidity	5% to 95% without condensation

Installation Notes

Footprint: An area of no less 15.9" (W) x 16.7" (L) x 4.36" (H) is recommended to properly install the cash drawer. Additional clearance is required in front of the drawer to allow the drawer to open. Optional mounting brackets for under-the-counter installation are available.

Power and Cabling: The cash drawer is powered from the interface cable when connected to a receipt printer's 24V cash drawer kick out port. A single cable provides both power and drawer interface. Make sure that the cable end labeled "Printer" is connected to the printer's cash drawer kick out port, and that the cable end labeled "Cash Drawer" is connected to the port on the back of the cash drawer.

Moisture: The cash drawer is not water-resistant. Accordingly, units should not be installed in areas where they might be exposed to direct water spray. Units are not intended for outdoor installation.